

Technical Data Sheet

Bitumen Sealant

Roof sealant based on bitumen. Waterproof, has good adhesion to various building materials, such as: wood, insulating panels, metal, plastic, concrete, tile, corrugated and sheet iron, etc. Excellent for quick repair of roofing, drainage systems, chimneys, gutters, can also be used in the construction of greenhouses, consolidation of cracks foundations. Can be used at low temperatures and on wet surfaces. After curing has excellent insulating properties. The cured sealant is resistant to UV radiation, constant humidity, abrasion and pressure.

DIRECTIONS FOR USE:

Clean the surface from dust, grease and other contaminants. Cut the cartridge tip and screw the nozzle tip, cut it in relation to the desired seam width. Using the gun put sealant evenly over the seam. The optimum bead width of 5 mm. Use at temperatures between +5°C to +40°C. Store in a cool, dry rooms and out of reach of children. Avoid direct sunlight and artificial radiation heaters.

PRECAUTIONARY MEASURES:

Harmful if inhaled. Irritating to eyes and skin. After contact with the sealant on the skin, rinse with water and, if necessary, consult a doctor.

The date of manufacture is indicated on the bottle.

Shelf life - 18 months.

TECHNICAL DATA:

NO.	Item	Data
1	Base	Bitumen
2	Density	1,03-1.10 g/cm ³
3	Color	black
4	Skin formation	20-30 minutes
5	Cutting time (5mm bead)	24-48 hours
6	Curing time	48-72 hours
7	Shelf life	18 months
8	Application temperature	from +5°C to +40°C
9	Temperature resistance	from -20°C to +80°C