

Technical Data Sheet

Liquid Nails

UNIVERSAL CONSTRUCTION GLUE

It is a one-component adhesive quick fix, is made on the basis of acrylic dispersion. Mounting adhesive is intended for gluing all building materials both indoors and outdoors. It has excellent adhesion to ceramic tile, brick, concrete, drywall, hard PVC and wooden products. Bonding strength 14-25kg/cm² for white and 21kg/cm² for transparent (wood-wood method).

DIRECTIONS FOR USE:

Clean the surface from dust, grease and other contaminants. Cut the cartridge tip and screw the nozzle tip, cut it in relation to the desired seam width. Use the glue gun to put glue on the surface with the stripes or dots. Firmly press bonding surfaces to each other and fix them in this position until the adhesive dries. Adhesive fixing time 5-20 minutes, time for complete drying glue 12-48 hours. Use at temperatures between +5°C to +40°C. Store in a cool, dry rooms and out of reach of children. Avoid direct sunlight and artificial radiation heaters.

PRECAUTIONARY MEASURES:

Store at temperatures between +5°C to +40°C, protect from frost.

Solvent-free, environmentally friendly.

The date of manufacture is indicated on the bottle.

Shelf life - 18 months.

TECHNICAL DATA:

NO.	Item	Data
1	Base	Acryl
2	Density	1,5 g/cm ³ white 1,0 g/cm ³ transparent
3	Color	White, transparent
4	Skin formation	5-20 minutes
5	Curing time	12-48 hours
6	Bonding strength (wood-wood method)	14-25 kg/cm ² white 21 kg/cm ² transparent
7	Shelf life	18 months
8	Application temperature	from +5°C to +40°C
9	Temperature resistance	from -25°C to +80°C