

Technical Data Sheet

Rubber Adhesive

It is a one-component adhesive sealant based on synthetic rubber. It is intended for sealing and repairing roofs from any type of metal tile, sealing gutters and drainage systems, sealing joints in window and door openings from any materials, sealing and gluing facade elements made of glass, concrete, PVC, etc. Constantly elastic, waterproof, transparent joint. It has excellent adhesion to most roofing materials. Temperature resistant in the range from -50°C to +180°C. Film formation time 5-10 minutes, full drying time 24-72 hours (5 mm seam).

DIRECTIONS FOR USE:

Clean the surface from dust, grease and other contaminants. Cut the cartridge tip and screw the nozzle tip, cut it in relation to the desired seam width. Using the gun put sealant evenly over the seam. The optimum bead width of 5 mm. Use at temperatures between +5°C to +40°C. Store in a cool, dry rooms and out of reach of children. Avoid direct sunlight and artificial radiation heaters.

PRECAUTIONARY MEASURES:

Harmful if inhaled. Irritating to eyes and skin. After contact with the sealant on the skin, rinse with water and, if necessary, consult a doctor.

The date of manufacture is indicated on the bottle.

Shelf life - 18 months.

TECHNICAL DATA:

NO.	Item	Data
1	Base	Polymer
2	Density	0,93-0,98 g/cm ³
3	Color	transparent
4	Skin formation	15-25 minutes
5	Cutting time (5mm bead)	12-24 hours
6	Curing time	24-48 hours
7	Elongation at break	>450%
8	Shelf life	18 months
9	Application temperature	from +5°C to +40°C
10	Temperature resistance	from -50°C to +180°C