

Technical Data Sheet

Aquarium Silicone Sealant

Designed for assembling and sealing aquariums, terrariums, other glass products. Has the best adhesive power, has excellent adhesion to non-porous materials, especially with glass. Can be applied to surfaces that come into contact with food. Can be used to seal the pools. Cured sealant retains excellent elastic properties and is easy to process. Resistant to ultraviolet. Full curing of the sealant - up to 24 hours (seam 5 mm). After 72 hours after curing, it is harmless to living organisms.

DIRECTIONS FOR USE:

Clean the surface from dust, grease and other contaminants. Cut the cartridge tip and screw the nozzle tip, cut it in relation to the desired seam width. Using the gun put sealant evenly over the seam. The optimum bead width of 5 mm. Use at temperatures between +5°C to +40°C. Store in a cool, dry rooms and out of reach of children. Avoid direct sunlight and artificial radiation heaters.

PRECAUTIONARY MEASURES:

Harmful if inhaled. Irritating to eyes and skin. After contact with the sealant on the skin, rinse with water and, if necessary, consult a doctor.

The date of manufacture is indicated on the bottle.

Shelf life - 18 months.

TECHNICAL DATA:

NO.	Item	Data
1	Base	Acetoxy
2	Density	0,92-0,95 g/cm ³
3	Color	transparent
4	Skin formation	15-25 minutes
5	Cutting time (5mm bead)	12-24 hours
6	Curing time	24-48 hours
7	Elongation at break	>450%
8	Shelf life	18 months
9	Application temperature	from +5°C to +40°C
10	Temperature resistance	from -50°C to +180°C