

Technical Data Sheet

Neutral Silicone Sealant

Suitable for sealing joints and cracks in kitchens, bathrooms, for sealing and bonding of non-porous vitreous surfaces. Ideal for sealing in wet areas. It has high water resistance, and is temperature resistant. Does not become darkened with time. It contains anti-fungal additives. Thermostable in the range from -50°C to +180°C. Film formation time 5-10 minutes. Complete drying takes 24-48 hours (in 5 mm wide seams).

DIRECTIONS FOR USE:

Remove dust, grease and other contaminants from surface. Cut the nozzle at the desired seam width and screw it to the cartridge. Using the appropriate gun apply the sealant evenly over the seam. An optimum bead width of 5 mm is recommended. Use at temperatures between +5°C to +40°C. Store in a cool, dry area and keep out of reach of children. Avoid direct long term exposure of cartridge to sunlight and artificial radiation heaters.

PRECAUTIONARY MEASURES:

Harmful if inhaled. Irritating to eyes and skin. In the event of contact of the sealant on the skin, rinse with water and, if necessary, consult a doctor.

The date of manufacture is indicated on the bottle.

Shelf life - 12 months.

TECHNICAL DATA:

NO.	Item	Data
1	Base	Oxime
2	Density	0,92-1,4 g/cm ³
3	Color	white, transparent
4	Skin formation	5-10 minutes
5	Cutting time (5mm bead)	12-24 hours
6	Curing time	24-48 hours
7	Elongation at break	>450%
8	Shelf life	12 months
9	Application temperature	from +5°C to +40°C
10	Temperature resistance	from -50°C to +180°C